Protac[™]

ScuffGuard

Protac™ Scuff Guard is a 6 mil (150µ) monomeric calendared PVC protective laminating film with a scuff -resistant, textured matte finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a single-sided, siliconised Kraft release liner. The anti-slip properties of Protac™ Scuff Guard have been tested in accordance with DIN 51130 standards and have been awarded an R10 rating.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN MEDIUM TO HIGH-TRAFFIC **INDOOR DISPLAY AREAS**
- PROVIDES UV PROTECTION FOR INDOOR AND OUTDOOR **GRAPHICS (UP TO 3 YEARS)**
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A **SCUFF-RESISTANT FINISH IS REQUIRED**
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC™ PRINT MEDIA TO CREATE A SLIP-RESISTANT FLOOR GRAPHIC

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film Matte Textured Monomeric Calendared PVC **Adhesive** Solvent Acrylic (Pressure Sensitive) **Release Liner** Siliconised 1 Side White Kraft

PRODUCT CHARACTERISTIC

Film Thickness 6 mil (150µ) **Adhesive Layer** 0.8 mil (20µ) Film contains UV stabilisers, **UV Protection Factor** which prevent film degradation and provide UV protection to the underlying image **Outdoor Durability** 5 Years **Service Temperature Range** -4°F to 203°F (-20°C to 95°C) >41°F (5°C) **Application Temperature Shelf Life** 1 year **Storage Conditions** 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature Speed Roller Laminator 1 ft to 8 ft (0.3m to Room temperature 2.5m) per minute to 104°F (40°C) Press Not recommended



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court, Brampton, Ontario, L6T 5A9, Canada toronto@drytac.com

Tel: +1 800.353.2883

USA

5601 Eastport Boulevard, Richmond Virginia, 23231, USA customerservice@drytac.com

Tel: +1 800.280.6013