

# Dynamic

Standard Gloss, Gloss Plus, Matte & Sandgrain

Dynamic films are monomeric PVC laminating films with a pressure sensitive, solvent acrylic adhesive and various finishes that provides superb color enhancement and UV protection. They also provides excellent durability and water resistance. For long-term outdoor applications, consider Interlam™ Pro, Protac™ or Weathershield® overlaminates as an alternative, based on longevity required for the application.

Dynamic Gloss Plus has an outdoor durability of 2 years.

- PHOTOGRAPHIC APPLICATIONS
- POP ADVERTISING
- POSTERS AND PRESENTATIONS
- EXHIBITION AND RETAIL SIGNAGE
- ROLLER BANNERS
- SUITABLE FOR SYNTHETIC SUBSTRATES.

## RECOMMENDATIONS

Edge-seal the print to give added protection, as this increases the durability of the adhesive.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Monomeric PVC <small>Standard Gloss, Gloss Plus, Matte &amp; Sandgrain finishes</small>
<b>Adhesive</b>	Solvent Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconized 1 Side PE Coated Kraft

### PRODUCT CHARACTERISTIC

	Standard Gloss, Matte & Sandgrain	Gloss Plus
<b>Film Thickness</b>	2.7 mil (70μ)   3.5 mil (90μ)	3.2 mil (80μ)   4 mil (100μ)
<b>Adhesive Layer</b>	0.8mil (20μ)	0.8mil (20μ)
<b>Film/Adhesive Ratio</b>	2.7:0.8	3.2:0.8
<b>UV Protection Factor</b>	UV stable	
<b>Outdoor Durability</b>	Not Applicable	2 Years
<b>Service Temperature Range</b>	-22°F to 158°F (-30°C to 70°C)	
<b>Shelf Life</b>	1 year	
<b>Storage Conditions</b>	59°F to 77°F (15°C to 25°C); 50 - 55% Relative Humidity	

# DRYTAC®

## ADHESIVE SCIENCE

### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)