

# SpotOn®

## Floor 200

SpotOn® Floor 200 is a print media for short-term, indoor floor graphics without the need for lamination. It boasts a post-printed R-10 anti-slip rating, which allows for vibrant, slip-resistant floor graphics. SpotOn® Floor 200 has been specifically developed for a simple, easy and tool-free installation. Thanks to a unique dot-pattern printed pressure-sensitive polyacrylate adhesive, this film can be applied to multiple flooring surfaces including short pile carpets, floor or ceramic tiles, sealed wood, concrete, waxed vinyl, marble, terrazzo surfaces and more. It can also be cleanly and quickly removed within six months of application.

- IDEAL FOR SHORT TERM INDOOR FLOOR APPLICATIONS

- EASY TOOL FREE APPLICATION

- CAN BE REMOVED EASILY WITHIN 6 MONTHS

**Product Code: SPOW**

**200** White Monomeric PVC  
micron

Matte

 (Eco)Solvent Latex UV

 DOT Pattern Polyacrylate Adhesive

 Widths up to 1370mm

 6 MONTHS DURABILITY INTERIOR

**SLIP-CERTIFIED WITHOUT LAMINATION**



### APPLICATIONS

APPLIED TO FLOOR,  
CERAMIC TILES,  
SEALED WOOD,  
CONCRETE, WAXED VINYL,  
SHORT PILE CARPETS



Certified for  
HP Latex Inks

**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# SpotOn®

## FLOOR 200

SpotOn® Floor 200 is a 200µ (8 mil) embossed printable white matte monomeric PVC film, coated on one side with a dot-pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single sided, siliconised clay coated kraft release liner. This high quality ink receptive embossed white vinyl was specifically developed for easy application. SpotOn® Floor 200 has a post-printed anti-slip rating of R10, according to DIN 51130:2010, which allows for vibrant, slip resistant floor graphics without the need for lamination.

- IDEAL FOR SHORT TERM INDOOR FLOOR GRAPHIC PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 6 MONTHS

### INSTALLATION RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	White Matte Monomeric PVC
<b>Adhesive</b>	Dot-Pattern Removable Polyacrylate
<b>Release Liner</b>	135 gsm Siliconised 1 Side Bleached Clay Coated Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	8 mil (200µ)	} 8.8 mil (215µ)
<b>Adhesive Layer</b>	0.6 mil (15µ)	
<b>Film/Adhesive Ratio</b>	8.0:0.6	
<b>UV Protection Factor</b>	Not Applicable	
<b>Outdoor Durability</b>	Internal Use Only	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	-4°F to 149°F (-20°C to 65°C)	
<b>Slip Rating</b>	R10 (According to DIN 51130:2010)	
<b>Shelf Life</b>	2 years	
<b>Storage Conditions</b>	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

PRINTING RECOMMENDATIONS  
UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013